

ASSEMBLY INSTRUCTIONS

for 4' & 5' wooden benches

*(To view a picture of a fully assembled bench
see the website of your purchasing company.)*

1. Unpack kit, review hardware. It should include the following:
 - (4) 1/4" x 2 3/4" carriage bolts w/ nuts
 - (6) 1/4" x 3 1/4" carriage bolts w/ nuts
 - (2) 1/4" x 2" carriage bolts w/ nuts *(except for 4' High-Back Heart Bench)*
 - (2) 1/4" x 3" lag bolt

Tools required

7/16" Socket or open end wrench
Hammer

2. Begin by bolting the back section to the seat section:
 - Use (4) 1/4" x 2 3/4" bolts, two bolts at each end. Tighten nut securely.
 - Use (2) 1/4" x 2" bolts in the center of the glider *(except for 4' High-Back Heart Bench)*Tighten nut securely.
3. Fasten left and right arms, making sure straight edge of the arm is toward the inside of the bench seat.
Begin by inserting (1) 1/4" x 3 1/4" bolt through arm and on the bench back section. Tighten with nut.
Lay bench on its back and insert (2) 1/4" x 3 1/4" bolts through legs into the bench seat.
Tighten nut onto bolt
Follow this same procedure to attach the arm on the other side.
4. Position bench face down and install back legs w/ attached brace.
Insert 1/4" x 3 1/4" bolts through pre-drilled holes in leg and seat. Tighten nut onto bolt.
Insert (1) 1/4" x 3" lag bolt in each outside leg in pre-drilled holes.
5. Be sure all screws and nuts are tight and securely fastened.